

LAURA ASHLEY



IL2804

GRAND VIENNA CRYSTAL PENDANT CEILING FITTING INSTALLATION INSTRUCTIONS

These instructions are provided for your safety.

Please read carefully before commencing work and retain for future reference.



SAFETY INFORMATION

- * If you are in any doubt consult a person competent to give advice on the installation of electrical equipment.
- * This fitting should be fitted in accordance with IEE Wiring Regulations and the Building Regulations
- * To prevent electrocution switch off at the mains supply before installing or maintaining this fitting. Ensure other persons cannot restore the electricity supply without your knowledge.
- * To avoid damage to concealed wiring during installation, establish the direction of the supply cable before drilling fixing holes.
- * This fitting is Class I =  and should be fitted to a lighting supply (with earth) protected by a 5 amp fuse or equivalent circuit breaker.
- * Always be sure to use the correct type and wattage of bulbs as indicated on the fitting. Never exceed the wattage stated.
- * When changing the bulb, always switch off at the mains and allow the old bulb to cool down before handling. Dispose of used bulbs carefully.
- * This fitting is designed for use with self-shielded tungsten halogen lamps only = 

THIS FITTING IS VERY HEAVY AND WILL REQUIRE A MINIMUM OF 2 PEOPLE TO INSTALL

INSTALLATION

There is some assembly required on this item after installation to fit the crystals on the top ring. Please leave all protective packaging on the droppers already fitted to the pendant until it is mounted on the ceiling to prevent any damage.

1. Ensure the house electricity supply is off at the fuse board.
2. If you are fitting this product in place of an existing one, you may find that there are more than 3 sets of cables connected. If there are loop in cables that are not connected to the light these must be terminated in a separate terminal block not connected to the fitting. Before removing existing fitting, carefully note position of each set of cables
3. **Do not remove protective packaging from crystals while installing fitting.**
4. Remove mounting bracket from the packaging then using as a template, mark and then drill the fixing holes in the ceiling. Ensure that the holes are drilled into a joist or other suitable mounting and not just the plaster.
5. Fix the mounting bracket to ceiling using suitable fixings. **Take care not to damage wiring.** ①
6. Chain links may be adjusted at this stage to reduce height of the pendant by using two pairs of pliers to open and close the chain links as required. Pull excess cable through the ceiling cup. Cloth should be used between jaws of the pliers to protect decorative finish. **Ensure that the chain is supporting the weight of the fitting and no strain is placed on the cable.** There are also suspension wires attached to the ceiling cup to balance the fitting out once installed so that it sits completely flat. To shorten the suspension wires these can simply be pushed through the tube into the ceiling cup and the tube will automatically lock so that when pulled the wire will not come back through. If you wish to extend the length of the wires simply push the small centre tube which is spring loaded in on itself to allow the wire to be pulled back out of the cup. Once the length is achieved simply release the tube and this will lock the suspension wire from pulling any further.
7. Loosen the ceiling cup cover side screw so that it drops down the upper stem above the chain exposing the hook and wiring. Hang the hook onto the mounting bracket to take the weight of the fitting while it is wired to the mains supply.
8. Weight of the fitting must be supported whilst you make the make electrical connections as follows: ②
Connect the supply live (normally brown or red) to fitting live (marked "L") on the terminal block.
Connect the supply neutral (normally blue or black) to fitting neutral (marked "N") on the terminal block.
Connect the earth (normally green/yellow or unsheathed) to terminal block marked '' on the fitting.
Ensure electrical connections are tight and no loose strands of wire are left out of the connector block.
9. With the wiring connected and secured carefully slide the cup up and over the wiring until it sits flush to the ceiling. Secure the cup in place by tightening the screw to lock against the stem in the side. ③ Take care not to trap wires in the process. Now with the fitting supported on the chain ensure that the suspension wires are adjusted so that the ring sits level, carefully adjust each wire a little at a time taking care to ensure that the centre chain is supporting the main weight of the fitting.
10. Fit the bulbs, type and wattage as indicated on the fitting. ④ **The wattage indicated must not be exceeded.** Use only self shielded bulbs  Do not touch halogen bulbs with bare hands as this will shorten their lives.

LAURA ASHLEY

IL2804

11. Help may be required to assist with fitting the crystals. Carefully unpack the crystals that attach to the top ring from the packaging. The crystals are supplied with a clip so that they can be easily attached onto each hole around the perimeter of the top ring. Push the clip through the hole from the outside and then fold over to retain the clip in position. Take care to prevent damage to the crystals or fitting.
12. Taking your time carefully remove all the packaging from the crystals on the underside of the fitting that were already attached.
13. Switch on the electricity supply at the fuse board.

GENERAL INFORMATION

This fitting is designed for internal use only and must be fitted to a DRY SURFACE as any dampness in plaster or paint can damage the finish. **Do not use polish or abrasive cleaner - just a soft dry cloth.**

