

# LAURA ASHLEY

IL2507

## CARSON CHANDELIER INSTALLATION INSTRUCTIONS

These instructions are provided for your safety.

Please read carefully before commencing work and retain for future reference.

### SAFETY INFORMATION

- \* If you are in any doubt consult a person competent to give advice on the installation of electrical equipment.
- \* This fitting should be fitted in accordance with current IEE Wiring Regulations and Building Regulations.
- \* To prevent electrocution switch off at the mains supply before installing or maintaining this fitting. Ensure other persons cannot restore the electricity supply without your knowledge.
- \* To avoid damage to concealed wiring during installation, establish the direction of the supply cable before drilling fixing holes.
- \* This fitting is Class I =  $\frac{1}{\text{I}}$  and should be fitted to a lighting supply (with earth) protected by a 5 amp fuse or equivalent circuit breaker.
- \* Always be sure to use the correct type and wattage of bulbs as indicated on the fitting. Never exceed the wattage stated.
- \* When changing the bulb, always switch off at the mains and allow the old bulb to cool down before handling. Dispose of used bulbs carefully.

### ASSEMBLY

This fitting is supplied with the stem separated to reduce packaging waste, to assemble please follow the instructions below:

1. Screw the stem into the main body of the fitting taking care to remove any plastic cable protectors that are fitted to prevent damage to the cable during transit. Ensure that the stem is tight and that the crystal is aligned how you would like to the arms.
2. Fix the stem in position by tightening the grub screw located in the side, ensure that this is secure.

### INSTALLATION

1. Ensure the house electricity supply is off at the fuse board.
2. Chain links may be adjusted to reduce the height of the fitting. Using two pairs of pliers, carefully open the chain links and remove the required number of links. Close the links. Note: Cloth should be used between the jaws of the pliers to protect the decorative finish. Pull any excess cable through the ceiling cup; making sure the chain is supporting the weight of the fitting and not the cable.
3. If you are fitting this product in place of an existing one, you may find that there are more than 3 sets of cables connected. If there are loop in cables that are not connected to the light these must be terminated in a separate terminal block not connected to the fitting. Before removing existing fitting, carefully note position of each set of cables
4. Remove the ceiling bracket from the ceiling cup by removing the 2 screws located in the side, retain the screws and any washers for later. Using the bracket as a template, mark and drill fixing holes in the ceiling. Ensure the holes are drilled into a joist or other suitable mounting and not just into plaster. Secure the bracket to the ceiling using suitable fixings.
5. The weight of the fitting must be supported whilst making the electrical connections as follows: Use a small flat bladed screwdriver to lever open the connector block housing.  
Connect supply live (normally brown or red) to fitting live (marked "L") on the terminal block.  
Connect supply neutral (normally blue or black) to fitting neutral (marked "N") on the terminal block.  
Connect supply earth (normally green/yellow or unsheathed) to earth (marked " $\frac{1}{\text{E}}$ ") on terminal block.  
**NOTE:** Ensure electrical connections are tight, no loose strands of wire are left out of the terminal block then fit rubber sleeve into place and close connector block housing by snapping together.
6. Mount the fitting by aligning the ceiling cup up over the bracket taking care to align the holes. Using the screws removed earlier fix the ceiling cup to the mounting bracket. Ensure that the fitting is securely attached and **take care not to damage wiring.**
7. Fit the bulbs: Type and wattage as indicated on the fitting. **The wattage indicated must not be exceeded.**
8. Switch on the electricity supply at the fuse board.

### GENERAL INFORMATION

This fitting is designed for internal use only and must be fitted to a DRY SURFACE as any dampness in plaster or paint can damage the finish. **Do not use polish or abrasive cleaner - just a soft dry cloth**

# LAURA ASHLEY

IL2507

